SAN AGRO

Spring Loaded Cultivator for Reliable Field Preparation

Designed for tough soil conditions, ensuring long-lasting performance and easy tillage.



30~45 HP Compatible | 5 Tine & 11 Tine Options | Spring Loaded | Efficient Soil Tillage



About Us.

SANAgro, the primary agricultural machinery division of SANAutomotive,focuses on delivering robust and efficient solutions for modern farming. With strong engineering and manufacturing capabilities, we offer a wide range of agri-equipment designed for tough field conditions—including rotary tillers, laser levellers, baler, combine harvester and other soil-preparation and land-management implements.

Heavy Duty Spring Loaded Cultivator

PARTICULARS	9 Tine	11 Tine
FRAME	75 x 40 mm channel	75 x 40 mm channel
SPRING	10 mm WD,50 mm OD	10 mm WD,50 mm OD
TINES	50 x 25 mm forged	50 x 25 mm forged
PAIRS	50 x 8 mm flat	50 x 8 mm flat
ANCHOR PIN	25mm	25mm
SHOVELS	8 mm En-45Reversible	8 mm En-45Reversible
FRAME BOLT	12 x 32 High Tensile	12 x 32 High Tensile
3POINT LINKAGE	65x12 & 50 x 12 mm	65x16 & 50 x 16 mm
HEIGHT	530 mm	530 mm
LENGTH	2000 mm	2450 mm
WIDTH	700 mm	700 mm
TILLER PIN	28 mm (Standard)	28 mm (Standard)
POWER REQUIRED (HP)	30-35 HP	40-45 HP
APPROX WEIGHT	275 Kg.	315 Kg.

Pin to Pin Spring Loaded Tiller



WWW.SANAUTOMOTIVE.COM

Tines	9 Tine	11 Tine
OVER ALL WIDTH	86 inches	106 inches
MAXIMUM WORKING WIDTH	80 inches	100 inches
OVER ALL HEIGHT	33.3/4 inches	34 inches
OVER ALL WEIGHT	210 kg	280 kg
UNDER FRAME CLEARANCE	15 inches	15 inches



WWW.SANAUTOMOTIVE.COM

Strength That Works. Performance You Can Trust.

Manufacturers of Heavy-Duty Agricultural Implements

Phone
+91 96507 93507

Website
www.sanautomotive.com

Mail
sanagro@sanautomotive.com